


KOBAU Armiera® Anstrichvlies



Type of crack / symbol



Field of application / properties

KOBAU Armiera® Anstrichvlies is intended for the reinforcement of paint systems in case of plaster surface cracks type A.1 according to the classification in the BFS notice no. 19. Due to the regular glass fibre structure, surfaces of high quality are also achieved in the field of dry construction and interior work. Thanks to the use of a special binder, KOBAU Armiera® Anstrichvlies is watertight, weatherproof, resistant to chemicals and non-fouling.

The reinforcing adhesive is unsuitable for processing Armiera Anstrichvlies.

For use inside and outside.

Processing

Prepare the substrate to be reinforced according to the national regulations and/or BFS notices. Subsequently, apply pasty dispersion paint with a high binder content until saturation using a roller or spray gun. Embed KOBAU Armiera® Anstrichvlies from the roll or as a ready-cut in the wet paint avoiding wrinkle formation or bubbles. Glue the outside of the roll towards the wall and always apply in the same direction. The webs should overlap in a width of approx. 5 cm. Separate with a double cut and remove both lateral strips. Join the light fleece KOBAU Armiera® Anstrichvlies seamless with a butt joint. Press the butt area against the substrate so that it is level. Subsequently, uniformly apply another coat of embedding material. Subsequent work is to be performed observing the instructions of the manufacturer in each case.

Technical data

Quality	▶ Textile glass fibre
Colour	▶ natural white
Stabilization	▶ PVA
Spec. weight DIN 53854	▶ abt. 35 g / m ²
Thickness	▶ abt. 270 µm
Max. longitudinal tensile force	▶ > 140 N / 5 cm
Max. transverse tensile force	▶ > 120 N / 5 cm
Longitudinal elongation	▶ -
Transverse elongation	▶ -
Loss on red heat	▶ < 24 %

Delivery form

Roll dimensions: 1.00 m x 50 m
 0.05 m x 10 m or 50 m
 0.10 m x 10 m or 50 m
 0.15 m x 10 m or 50 m
 0.20 m x 10 m or 50 m
 (other dimensions on request)

Tools

- Roller, brush or sprayer
- Cutter knife, paperhanger's spatula

Tools

Glass fabric adhesive or pasty dispersion approx. 400 - 500 ml / m²

Storage

dry, cool, in closed spaces

Note

Perform subsequent work taking into account the instructions of manufacturer in each case.

The above statements reflect the current stage of development and make no claim to be exhaustive. As the application and use of our product is beyond our control and variations in use, modes of operation and materials must be tailored to the prevailing working conditions, this technical information cannot be regarded as legally binding. This edition supersedes previous technical instructions.